

ABOil Solar Flare III 5W-30

Passenger Vehicle Engine Oil

Product number: 594315

Product description

ABOil Solar Flare III 5W-30 is a low-ash, synthetic engine oil for up-to-date engines. It offers high reliability and allows maximum reduction of fuel consumption.

- Modern high-performance oil, minimizes wear by rapid oil circulation, especially in the warm-up phase of the engine, allowing maximum loads and provides high safety reserves.
- Resistance to aging and secures operation within the specified oil drain interval
- Latest additive technology keeps the engine clean, reduces friction and guarantees maximum engine lifetime

Quality Level

ACEA C3
API SN/CF
BMW LL-04
Fiat 9.55535-S3
GM dexos2
MB 229.51, 229.31, 226.5
Opel OV 040 1547 – D30
Renault RN 0700, RN 0710

Application

ABOil Solar Flare III 5W-30 can be used in many modern passenger cars, gasoline and diesel engines with DPF, especially for BMW, Mercedes-Benz, Renault and Opel.

Property	Test method	Value
Density @ 15 °C, kg/m ³	DIN 51757	854
Flash Point, COC, °C	ISO 2592	≥215
Kinematic viscosity @ 40 °C, mm ² /s	DIN 51562/T1	71,7
Kinematic viscosity @ 100 °C, mm ² /s	DIN 51562/T1	12,1
Viscosity index	DIN ISO 2909	166
Pour Point, °C	DIN ISO 3016	≤-39
Total Base Number, mg KOH/1 g oil	ASTM D 2896	7,4

All data are average values and are subject to production-related fluctuations. Technical data are subject to change. Please observe the instructions of the machine manufacturers!

Version 1.0 created
11.12.2024

Page 1 of 1

PDS_EN_594315_ABOil Solar Flare III 5W-30.docx